LUMIPLUS ESSENTIAL MINI PROJECTOR FOR WALL BUSHING


Wall bushing mounted .



		76681	76681WW
E	Color	White	Warm White
	Consumption	4 W (6 VA)	
	Luminous flux	315 lm	
	Temp. Color	5.700 K	3.000 K

		76683
G	Color	RGB
	Consumption	4 W (7 VA)
	Luminous flux	186 lm
	Remote Control	Not included
	Control	Can be controlled by push-button 32458, LumiPlus Range Extender 64633 + RC1100 remote controller 75773 or LumiPlus Connect controller 76290.

VOLTAGE:	12 V AC
FREQUENCY:	50/60 Hz
SERVICE LIFE:	L70-50,000 h
MAX. WATER TEMPERATURE:	40 ºC
MAX. INSTALLATION DEPTH:	2 m
MAXIMUM WATER TREATMENT VALUES:	
	Chlorine: 2 mg/l Bromine: 5 mg/l Salt chlorinator (NaCl): 6 g/l Pool water pH: 7.2 and 7.6
CABLE:	2.5 m. H07RN-F 2 x 1 mm^2
MATERIALS:	Polyamide
WALL BUSHINGS:	53956/15661
DECORATIVE RINGS:	Beige: 77328CL090 Grey: 77328CL129 Anthracite: 77328CL144



IP 68

PACKAGING AND PALLETIZATION

Volume/Single box (m^3)	0,003
Weight/Single box (kg)	0,58
Units/Standard box	4
Volume/Standard box (m^3)	0,026
Weight/Standard box (kg)	2,50
Units/Pallet	400
Volume/Pallet (m^3)	2,30
Weight/Pallet (kg)	275

SINGLE BOX



MULTIPLE BOX

